



PUSHER RAM TRAILERS

A HEAVY DUTY DESIGN FOR HIGH PERFORMANCE

PROVEN IN THE FIELD

CONTACT US

**+44(0)1728 723224 • sales@richardwestern.com
Richard Western Ltd, D'Urbans, Framlingham, Suffolk IP13 9RP**

Pusher Ram Trailers

Large volume for efficient transport and less downtime, increase the efficiency to your forage harvester. Unrivalled construction provides tremendous strength, minimal maintenance costs and long life.

STANDARD FEATURES

- 8mm Floor and 5mm Sides (S355mc Steel)
- 10 Stud commercial axles
- Torque Arm Suspension to suit large diameter agricultural wheels
- The height adjustable sprung drawbar with Bolt-On ring hitch
- The sides and floors are each made in one piece of steel
- Sliding system is low maintenance
- Pusher blade is supported by 4 industrial wheels to reduce friction while the seal is also made of PE1000 thermoplastic for high wear resistance
- Stability during unloading; it can even be unloaded in a building; cargo can also be partially unloaded
- Quick unloading cycle time
- Locking tailboard for compressing resistance
- Opening and locking the tailgate has a hydraulic and mechanical lock function for added security
- Tandem axle version operates from the tractors hydraulics. Tri axle model PTO driven on board hydraulics
- Air Brakes

Optional Equipment:

- Hydraulic suspension
- Passive steering axle
- Active steering axle
- Hydraulic brakes in lieu of air brakes or dual air and hydraulic brakes with LSV
- ABS on Air brakes
- Auto slack adjusters
- Front to back roll over sheeting system
- Load cell weigher complete with separate chassis



Pusher Trailer Model	Capacity	Body Width External	Body Width Internal	Body Length	Overall Length	Loading Height
PR3018	30(m ³)	2.55m	2,24m	5,61m	7,51m	3,74m
PR3621	36(m ³)	2.55m	2,24m	6,63m	8,53m	3,74m
PR4024	40(m ³)	2.55m	2,24m	7,31m	9,21m	3,74m
PR5030	50(m ³)	2.55m	2,24m	9,00m	10,91m	3,74m