



SDS MANURE SPREADERS

A HEAVY DUTY DESIGN FOR HIGH PERFORMANCE

PROVEN IN THE FIELD

**+44(0)1728 723224 • sales@richardwestern.com
Richard Western Ltd, D'Urbans, Framlingham, Suffolk IP13 9RP**

CONTACT US

SDS Manure Spreaders

STANDARD FEATURES:

- 590mm diameter by 1500mm wide spreading rotor
- Reversible bolt on face plates on rotor and centre auger
- Double acting hydraulic side door
- Spring steel auger discharge paddle
- Heavy duty construction
- Up to 16 metres wide even spread
- RTA lights
- 15 tonne hydraulically braked axle / Tandem option SDS24
- 3 stage reduction gearing
- Hydraulically operated stone trap

A heavy duty chain drive is used to power the large diameter spreading rotor and the hydraulically operated guillotine type side door allows you to control application rates.

Option of Hydraulic Version

Two high torque hydraulic motors are used to drive the internal floor auger and a heavy duty chain drive is used to power the large diameter spreading rotor. This is best suited to sand slurry lagoon spreading, as the auger can be run independently of the rotor. This helps keep semi solids suspended in the liquid.

A hydraulically operated guillotine type side door allows you to control application rates.

Optional Equipment:

- Flashing beacon
- Rear drawbar c/w brakes and electrics
- Power flow auger
- Wide angle PTO shaft
- Hydraulically driven main auger in lieu of chain driven main auger
- Air brakes

