

**RICHARD
WESTERN**
PROVEN IN THE FIELD

RICHARD
WESTERN
PROVEN IN THE FIELD
50
YEARS
Making Trailers



DELILAH VERTICAL BEATER MANURE SPREADER
RELIABLE PERFORMANCE, ACCURATE SPREADING

The Delilah 4000 series models are constructed with 6mm floor panels and 4mm side panels. The floor is hydraulically driven with two floor chains and a single floor slat. 16mm floor chains are used up to and including D4120 with 65mm rear floor shaft. 20mm floor chains and larger slats on the D4130 & D4150 machines with 80mm rear floor shaft. The body is 1550mm wide with a flared top to create a wider top area for easy loading and less spillage. Rotors are 890mm diameter on the D4120 and below and 1100mm diameter on the D4130 and above. With large diameter rotors and a high tip speed the Delilah 4000 series spreaders offer wide spreading width and excellent shredding on a wide range of manures, composts and sludges.



The new 1100mm diameter rotors have a disc base with three blades and replaceable wearing-parts. The option of a hydraulic folding canopy door allows the spreader to be used as a vertical beater spreader or with the doors closed the spreader can be used as a spinning disc spreader. The large diameter rotors are fitted as standard on the D4120 and D4150 and optional on the D4100.



STANDARD FEATURES

- Fixed Drawbar
- Hydraulic Brakes
- Variable speed hydraulic floor drive
- Wide angled PTO shaft with shear bolt protection and rattle clutch

OPTIONAL EXTRAS

- Air Brakes
- Hydraulic slurry door
- Sprung drawbar
- Greedy Boards
- Rear drawbar with brakes and electrics
- Electronic bed speed control
- Weighing equipment with display mounted on the spreader 4 weigh cells
- Hydraulic Folding Canopy Door for 1100 Rotors only

SPECIFICATION

	D4080	D4095	D4100	D4120	D4130	D4150
Body Length*	4.10m	5.14m	5.14m	6.10m	6.10m	6.10m
Body Depth	1.24m	1.00m	1.24m	1.24m	1.24m	1.50m
Body Width Top	2.10m	2.10m	2.10m	2.10m	2.10m	2.10m
Body Width Bottom	1.55m	1.55m	1.55m	1.55m	1.55m	1.55m
Loading Height	2.40m	2.40m	2.40m	2.40m	2.55m	2.55m
Overall Height	3.34m	3.09m	3.34m	3.34m	3.34m	3.59m
Overall Width	2.99m	2.99m	2.99m	2.99m	2.99m	2.99m
Overall Length	6.33m	7.31m	7.31m	8.31m	8.31m	8.31m
Cubic Capacity**	8.00m ³	8.00m ³	10.30m ³	12.20m ³	12.20m ³	14.40m ³
Floor chains	2x16mm	2x16mm	2x16mm	2x16mm	2x20mm	2x20mm
Floor drive shaft	65mm	65mm	65mm	65mm	80mm	80mm
Rotor diameter	890mm	890mm	890mm	890mm	1100mm	1100mm
Number of Axles	1	1	1	1	1	1
Wheels	23.1x26	23.1x26	580/70R38	580/70R38	580/70R38	580/70R38
Tare Weight	4895kg	5530kg	5530kg	5530kg	5825kg	5825kg

* Body length is measured without slurry door

** Cubic capacity is level filled with no slurry door

Richard Western Ltd., D'Urbans, Framlingham, Suffolk, IP13 9RP
 t: 01728 723224 e: sales@richardwestern.com
richardwestern.com